

Alpha XL 4/266 WorkStations

START

#1	Order Number	Oper. System	Aplic.	WorkStations, 64Bits	266MHz
	SN-A21AA-NP	Windows NT	CAD 3D	32MB 2MB RX,CD 1GB (no NI)	120V, U.S.
	SN-A21WW-CP	Windows NT	CAD 3D	32MB 2MB RX,CD 1GB (no NI)	240V Worldwide

#2 SVGA Color Monitor

#3	Monitor
	SN-PCXBV-YA/YC 15"
	SN-PCXAV-EC/ED 17"
	SN-PCXAV-ZB/ZC 21"
	NH/SH

Country Kit for 240V Use

SN-PCAIN	-AE (GB)	-AH (NL)	-AN (N)
- keyboard	-AB (B)	-AI (I)	-AP (F)
- power cord	-AD (DK)	-AK (CHF)	-AS (E)
- mouse	-AF (FI)	-AL (CH/G)	-AT (IL)
- user doc.	-AG (D)	-AM (S)	-AV (P)
- Windows NT license + doc.			

240V Power Cord for Monitor

#4	1x BN19C-2E EUROPE	BN19A-2E (GB)	BN19K-2E (DK)	BN19M-2E (I)
		BN19E-2E (CH)	BN18L-2E (IL)	BN19S-2E India

Internal Options:

Memory Expansion



SN-PC77M-AC	32MB kit	System	Max memory
SN-PC77M-AD	64MB kit	kit kit 32 MB	3x 128MB
SN-PC77M-AJ	128MB kit		= 384MB

Internal Storage


SN-PCXCR-AN	600MB CD-ROM drive
SN-PCXAT-AF	4/8GB DAT-tape drive
SN-PCXAT-AD	2/4GB QIC-tape drive
SN-PCXRE-AA	1.05GB hard disk
SN-PCXAR-AY	2.0GB hard disk
SN-PCXAR-AZ	4.0GB hard disk

Controllers

KZPAA-AA	PCI-based Fast SCSI-2 Controller, narrow
DE435-AA	PCI-based Ethernet Controller
SN-PCXTN-AB	ISA-based TokenRing
PBXGA-AN	PCI-based ZLXp-E1 8PL Graphics
PBXGA-BN	PCI-based ZLXp-E2 24PL Graphics
PBXGA-CN	PCI-based ZLXp-E3 24PL Z Graphics



External Options



SPECint92	SPECfp92
199	263 266MHz

Software Processor Code: E

GEAW0XLB

digital	17-Apr-1996	Detail Layer
	GOLDaw00XL4266a	

Alpha XL 4/266 WorkStations

GOLDEN EGGS Visual Configurations, Helsinki

XL